



### DIN-2642 PN10 YAKA

ÖLÇÜ		d4	d1	s	h
DN 10	3/8"	40	17,2	2	9
DN 15	1/2"	45	21,3	2	9
DN 20	3/4"	58	26,9	2,5	12
DN 25	1"	68	33,7	2,5	15
DN 32	1 1/4"	78	42,4	2,5	15
DN 40	1 1/2"	88	48,3	2,5	17
DN 50	2"	102	60,3	3	23
DN 65	2 1/2"	122	76,1	3	23
DN 80	3"	138	88,9	3	23
DN 100	4"	158	101,6	3	28
		158	108	3	28
		158	114,3	3	28
DN 125	5"	188	125	3	30
		188	133	3	30
		188	139,7	3	30
DN 150	6"	212	151	3	30
		212	159	3	30
		212	168,3	3	30
DN 200	8"	268	219,1	3	30
DN 250	10"	320	273	3	30
DN 300	12"	370	323,9	3	35
DN 350	14"	430	355,6	3	35
DN 400	16"	482	406,4	4	40
DN 500	20"	585	508	4	45
DN 600	24"	685	609,6	4	45
DN 700	28"	800	711,2	4	45
DN 800	32"	905	812,8	4	45
DN 900	36"	1005	914,4	4	45
DN 1000	40"	1105	1016	4	45